



# Urea

## Prilled, Unconditioned (Industrial Grade)

### GUARANTEED ANALYSIS:

Assay, Wt%	98.9 min.
Total Nitrogen at N, Wt%	46.1 min.
Moisture as H <sup>2</sup> O, Wt%	0.5 max.
Alkalinity, As Ammonia, ppm	100 max.
Biuret, Wt%	0.6 max.
Iron, as Fe, ppm	2 max.
Ash, ppm	25 max.
pH, 10% Solution at 68° F	7.0 – 9.5

### PHYSICAL DATA:

Color, APHA	15 max, guaranteed
Turbidity, as SiO <sub>2</sub> , ppm	20 max, guaranteed
Size Range, U.S. Std. Mesh, Wt T	100, -5 99, +20
Bulk Density, lbs/ft <sup>3</sup>	45 – 48
Size Guide Number (SGN) as made:	200 Avg, 180-220 Range
Angle of Repose, degrees	28°

The information and data contained herein is based upon facts considered to be correct as of the date hereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will The Andersons, Inc. be responsible for damages of any nature whatsoever resulting from the use or reliance upon this information. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which this information refers.